

9602

- Iridium® communications transceiver
- Rugged and dependable design

metOcean
telematics

iridium®



TELEMATICS

The Iridium® 9602 transceiver leverages Iridium's low-latency SBD service and provides truly global coverage. The 9602 is designed to be integrated into wireless data applications with other host system's hardware and software to produce a complete telemetry solution. The 9602 meets the regulatory requirements for FCC, Canada and CE assuming an antenna with a gain of ~3 dBi and adequate shielding is used.



TECHNICAL SPECIFICATIONS

PHYSICAL	1.61" x 1.77" x 0.51"
Dimensions	41 mm x 45 mm x 13 mm
Weight	30 g

RADIO FREQUENCIES	
Operating Frequency	1616 to 1626.5 MHz
Duplexing Method	Time division duplex
Input/Output Impedance	50 Ω
Multiplexing Method	TDMA/FDMA

ENVIRONMENTAL	
Operating Temperature	-40°C to +85°C
Operating Humidity	≤ 75% RH
Storage Temperature	-40°C to +85°C
Storage Humidity	≤ 93% RH

DATA ID/O	
MO Message Size	340 bytes/message
MT Message Size	270 bytes/message

ELECTRICAL	
Input Voltage	5.0 V +/- .5 V DC
Input Ripple	< 40 mVpp
Idle Current Avg.	35 mA
Idle Current Peak	170 mA
Transmit Current Avg.	140 mA
Transmit Current Peak	1.3 A
Receive Current Avg.	40 mA
Receive Current Peak	170 mA
SBD Message Transfer Avg. Current	150 mA
SBD Message Transfer Avg. Power	< 0.8 W

HEAD OFFICE

MetOcean Telematics
21 Thornhill Drive
Dartmouth, Nova Scotia
Canada B3B 1R9
sales@metocean.com

+1 902 468 2505

UNITED STATES

MetOcean Telematics
1750 Tysons Blvd
Suite 1500, Office 1547
McLean, VA 22102
sales@metocean.com

+1 844 728 2868

UNITED KINGDOM

MetOcean Telematics
Hilldale Farm
Titchfield Lane,
Wickham, UK PO17 5NZ
sales@metocean.com

+44 1489 888 555

CANADA

MetOcean Telematics
2 Gurdwara Rd Suite 608
Ottawa, Ontario
Canada K2E 1A2
sales@metocean.com

+1 613 702 3196